

BID PACKAGE FOR FURNISHING
CITY OF WAVELAND STREETS
DEPARTMENT
HOT BITUMINOUS IN PLACE, HOT MIX ASPHALT
GRADES SC-1, SC-2, BC-1, BC-2

City of Waveland
301 Coleman Avenue
Waveland, MS 39576

BIDDER CONTACT INFORMATION DOCUMENT

Pursuant to your advertisement, receivable until 3:00 PM ON May 20, 2015, we _____ operating at _____ do hereby submit this our bid for furnishing, as ordered by the City, Hot Bituminous in Place, Hot Mix Asphalt – Grades SC-1, SC-2, BC-1, BC-2, and Ultra-Thin Asphalt Pavement as set out below, for a period beginning at bid acceptance and ending _____ or until a new bid is accepted.

DATE: _____

FIRM NAME OF BIDDER: _____

SIGNED: _____

NAME & TITLE: _____

ADDRESS OF FIRM: _____

CITY, STATE:- _____

PHONE: _____ FAX: _____

MS AUDITOR'S LICENSE NUMBER:- _____

NOTICE TO BIDDERS:

ALL BIDS SHOULD BE SUBMITTED ON THIS FORM, AND SHALL BE SUBMITTED IN A SEALED ENVELOPE MARKED "HOT MIX ASPHALT" TO BE OPENED AT _____

BIDS NOT SUBMITTED ON THIS FORM MAY BE DISQUALIFIED. THE CITY OF WAVELAND BOARD OF MAYOR AND ALDERMEN RESERVE THE RIGHT TO REJECT ANY AND ALL BIDS.

FOR INFORMATION CONTACT: CITY OF WAVELAND

301 COLEMAN AVENUE
WAVELAND, MS 39576
CITY CLERK: LISA PLANCHARD (228) 467-4134

SPECIFICATION DOCUMENT

- 1 HOT BITUMINOUS MIXES, SC-1, SC-2, BC-1, or BC-2, shall be in accordance Section 403, "Mississippi Standard Specifications for State Aid Road and Bridge Construction, 1989 Edition".
- 2 Ultra-Thin Asphalt Pavement, UHMA, shall be in compliance with Mississippi Department of Transportation Special Provision No. 907-411-4 issued 07-25-2013.

AGGREGATE, GRADATION AND BITUMEN CONTENT

All material, procedures and workmanship shall be in accordance with specifications referenced above.

- 3 Applies to asphalt placing operations only: At the option of the City Engineer and prior to any trucks being loaded at the plant site, an independent testing laboratory, appointed by the City Engineer, shall be notified by the asphalt plant to perform the following services:
 - A. PLANT INSPECTION
 - B. TEMPERATURE CONTROL OF ASPHALT PRODUCED
 - C. APPROVED DESIGN MIX FOR PROJECT
 - D. STABILITY AND EXTRACTION TEST
 - E. CERTIFICATION OF SCALES

ALL OF THE ABOVE TESTING TO BE PAID FOR BY OWNER

- 4 Asphalt placement operations shall not commence unless the outside air temperature in the shade is 50 degrees F and rising. This requirement may be waived at the discretion of the City Engineer.

GENERAL REQUIREMENTS

1. The asphalt plant producing the required mix may be inspected and approved by personnel from the Mississippi Department of Transportation. Proof of this inspection and approval must be provided to the City Engineer prior to placing mix.
2. Tickets from certified scales shall be issued for each load from the bidder's plant.
3. The engineer reserves the right to place an inspector at the plant to sign and certify scale tickets.
4. It is understood that labor and equipment includes water sprinkling to dampen a previously prepared base and/or prior to sweeping to reduce dust.
5. Existing Hard Surface Roadway shall have tack coat applied and shall be included in Bid Price for Hot Mix Asphalt in Place.
6. The City reserves the right to cancel contract to purchase at any time for justifiable cause. Further, contract to purchase may be canceled for any other reason by either party upon 30 days written notice.
7. The City reserves the right to place an inspector on the job site to verify quantities and quality of work.
8. Failure of the vendor to commence work, under the terms of this contract within ten (10) calendar days from the purchase order issue date, and depending on the scope of the project, complete such project within ninety (90) days, as determined by the engineer, will require said vendor to submit to the City Administrator a letter of explanation regarding such failure. After review of said letter, the City reserves the right to cancel such purchase order for cause and re-issue same to an accepted alternate bidder. Any excess cost occurring from the next lowest bidder will be charged to the lowest bidder.
9. This bid shall be utilized for a minimum project quantity as shown below. Asphalt may be used for "spot repair", therefore one purchase order may consist of more than one site, city-wide.
10. Contractor shall show Proof of Insurance and name City of Waveland as co-insured. See attached for required insurance limits.

The following proposal is made on behalf of
and no others. The bid is made without collusion on the part of any person, firm and/or corporation. We hereby certify that we have personally examined the specifications and have satisfied ourselves as to all conditions affecting the work.

HOT MIX ASPHALT BID

Furnish and place:

GRADES:

GRADE	PROJECT QUANTITY	UNIT	UNIT COST
SC-1	Less than 10 tons	TON	
SC-1	10.01 to 20 tons	TON	
SC-1	20.01 to 30 tons	TON	
SC-1	30.01 to 40 tons	TON	
SC-1	Greater than 40 tons	TON	
SC-2	Less than 10 tons	TON	
SC-2	10.01 to 20 tons	TON	
SC-2	20.01 to 30 tons	TON	
SC-2	30.01 to 40 tons	TON	
SC-2	Greater than 40 tons	TON	
BC-1	Less than 10 tons	TON	
BC-1	10.01 to 20 tons	TON	
BC-1	20.01 to 30 tons	TON	
BC-1	30.01 to 40 tons	TON	
BC-1	Greater than 40 tons	TON	
BC-2	Less than 10 tons	TON	
BC-2	10.01 to 20 tons	TON	
BC-2	20.01 to 30 tons	TON	
BC-2	30.01 to 40 tons	TON	
BC-2	Greater than 40 tons	TON	
Ultra Thin Asphalt Pavement, UHMA	Less than 10 tons	TON	
Ultra Thin Asphalt Pavement, UHMA	10.01 to 20 tons	TON	
Ultra Thin Asphalt Pavement, UHMA	20.01 to 30 tons	TON	
Ultra Thin Asphalt Pavement, UHMA	30.01 to 40 tons	TON	
Ultra Thin Asphalt Pavement, UHMA	Greater than 40 tons	TON	

VENDOR NAME _____

ADDRESS- _____

PLANT ADDRESS _____

DELIVER BID TO CITY OF WAVELAND
 CITY CLERK: LISA PLANCHARD
 301 COLEMAN AVENUE
 WAVELAND, MS 39576